

Stainless steel lifting eye screw DIN 580



Product information

Stainless steel lifting eye for vertical lifting.

Material: AISI 316

Marking: According to standard, CE-marked

Temperature range: -40°C - (+)200°C

Finish: Polished

Standard: DIN 580

Note: Only for vertical lifting

Warning: Not to be heat-treated

Safety factor: 4:1

Part Code	WLL ton	Thread mm	b mm	c mm	d mm	e mm	f mm	g mm	Weight kg	Delivery time
NSRH06L	0.08	M6	20	36	20	13	6	36	0.06	0
NSRH08L	0.14	M8	20	36	20	13	6	36	0.06	0
NSRH10L	0.23	M10	25	45	25	17	8	45	0.11	0
NSRH12L	0.34	M12	30	54	30	20.5	10	53	0.18	0
NSRH16L	0.7	M16	35	63	35	27	12	62	0.28	0
NSRH20L	1.2	M20	39	71	39	30	14	70	0.45	0

Technical data

WORKIN LOAD LIMITS



Thread	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
M6	0,08		0,16		-		-	
M8	0,14		0,28		0,1		0,14	
M10	0,23		0,46					

Blueprint

