
Steel Wire Rope 6x19M-WSC

Product information



Slings



Winch rope



Stay rope



Agriculture and livestock





ISO 4309 Rope Category No: All Diameters **RCN.04**

... *Read more*

Rope construction: 6x19M-WSC
Marking: According to standard
Standard: EN 12385-4

Fill factor: 0.53
RCN: 04

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Steel Wire Rope 6x19M-WSC

Technical data / Spare Parts

Part code	Rope diameter mm	Tensile strength N/mm²	Finish	Rope lay	Min. breaking force kN	Steel area mm²	Lubrication	Weight kg/100m
TEK13304	4	1,770	Galvanized	sZ	10.3	6.69	Dry	6.1
TEK13305	5	1,770	Galvanized	sZ	16	10.5	Dry	9.53
TEK13306	6	1,770	Galvanized	sZ	23.1	15	Dry	13.7
TEK13308	8	1,770	Galvanized	sZ	41	26.8	Dry	24.4
TEK13310	10	1,770	Galvanized	sZ	64.1	41.8	Dry	38.1
TEK13312	12	1,770	Galvanized	sZ	92.3	60.2	Dry	54.9

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved