



Steel Wire Rope 35x7 (Rotation resistant)

Product information



Typical applications: Hoist rope for tower cranes, mobile cranes, electrical hoists and other applications where rotation resistant rope is required.

ISO 4309 Rope Category No: All Diameters **RCN.23-2**

Rope construction: Rotation resistant, made out of conventional strands.

Marking: According to standard

Standard: EN 12385-4

Fill factor: 0.61

RCN: 23-2

Part code	Rope diameter mm	Tensile strength N/mm ²	Finish	Rope lay	Min. breaking force kN	Steel area mm ²	Lubrication	Weight kg/100m
ANKO08	8	2,160	Galvanized	sZ	48.4	30.7	A-1	29
ANKO10	10	2,160	Galvanized	sZ	75.6	48	A-1	45
ANKO12	12	2,160	Galvanized	sZ	109	69.1	A-1	65
ANKO14	14	2,160	Galvanized	sZ	148	94.1	A-1	89
ANKO16	16	2,160	Galvanized	sZ	194	123	A-1	116
ANKO18	18	2,160	Galvanized	sZ	245	156	A-1	147
ANKO19	19	2,160	Galvanized	sZ	273	173	A-1	164
ANKO20	20	2,160	Galvanized	sZ	302	192	A-1	182
ANKO22	22	2,160	Galvanized	sZ	366	232	A-1	220