Wire Rope Clamp BG

Product information



General: Wire rope clamp type, approved for lifting. Requires fewer clamps per fixation, e.g. two wire clamps instead of four, for 16 mm cable. Symmetrical – cannot be wrongly fitted. The clamps ensure fixation of the wire to a degree of at least 90% of the minimum breaking load of the wire in accordance with the current European standard.

Design: Bases of cast steel.

... *Read more*

Finish: Body Hot dip galvanized and bolt electro galvanized
Note: Follow the fitting instructions in the user manual before use. Not for use with compacted or hammered wire ropes.

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Wire Rope Clamp BG

Technical data / Spare Parts

Part code	Rope Ø range mm	Thread	No. of clips when lifting	Torque Nm	Weight kg/100pc
VLBG06	5-6	M6	2	9,5	9
VLBG08	6.5-8	M6	2	9,5	12
VLBG10	8.5-10	M8	2	22	20
VLBG12	11-12.5	M10	2	44	39
VLBG16	13-16	M12	2	75	72
VLBG20	17-20	M14	2	120	120
VLBG25	21-25	M18	2	260	280
VLBG34	26-34	M20	2	350	770

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved