

Lift graded turnbuckles with open frame

Product information

Lift graded turnbuckle for professional use. Equipped with locking nuts and fork/fork ends.

Material: SAE 1035 special steel

Marking: WLL | size marks

Finish: Hot dip galvanized

Safety factor: 5:1



| Part code | WLL ton | MBL ton | Thread | A mm | B mm | C mm | D, mm | Weight kg | Delivery time days |
|-----------|---------|---------|------------|------|------|------|---------|-----------|--------------------|
| VR3/8 | 0.54 | 2.7 | 3/8"x6" | 12 | 21 | 8 | 273-409 | 0.57 | 21 |
| VR1/2 | 1 | 5 | 1/2"x9" | 16 | 26 | 10 | 380-587 | 1.18 | 21 |
| VR5/8 | 1.59 | 7.95 | 5/8"x9" | 18 | 32 | 13 | 421-622 | 2.12 | 1 |
| VR3/4 | 2.36 | 11.8 | 3/4"x9" | 24 | 38 | 16 | 422-639 | 3.03 | 21 |
| VR7/8 | 3.27 | 16.35 | 7/8"x12" | 27 | 42 | 19 | 559-825 | 4.9 | 21 |
| VR1 | 4.54 | 22.7 | 1"x12" | 30 | 50 | 22 | 598-859 | 6.96 | 1 |
| VR11/4 | 6.9 | 34.5 | 1 1/4"x12" | 44 | 71 | 28 | 641-916 | 11.9 | 21 |
| VR11/2 | 9.71 | 48.55 | 1 1/2"x12" | 52 | 71 | 35 | 675-941 | 16.9 | 21 |

Blueprint

