

Lift graded turnbuckles with closed body

Product information

Lift graded turnbuckle for professional use. Equipped with locking nuts and fork/fork ends.

Material: Steel

Marking: CE-marked, WLL | batch | Haklift

Finish: M6/M8 electric galvanized | M10-M52 hot dip galvanized

Safety factor: 5:1



Part code	WLL ton	Thread	A mm	B mm	C mm	D, mm	E mm	G, mm	dmm mm	h mm mm	L1mm mm	L min. mm mm	L max. mm mm	Weight kg	Delivery time days
VRH06	0.2	M6	19	7	16	14.5	100	12	M5	6.5	54	180	255	0.13	1
VRH08	0.32	M8	23	9	22	17.2	108	14	M6	8.5	59	210	285	0.25	1
VRH10	0.5	M10	26	10	21	17.2	150	17	M8	7	79	250	360	0.3	1
VRH12	0.7	M12	33	13	26	21.3	195	22	M10	8	106	330	480	0.65	1
VRH16	1.2	M16	42	18	32	27	230	26	M12	8	122	395	580	1.25	1
VRH19	1.5	M20	50	20	38	34	270	32	M16	12	145	460	680	2.2	1
VRH22	2.2	M22	44	25	50	34	295	46	M20	12	160	500	720	3.3	1
VRH25	3.2	M24	51	28	54	42	325	52	M22	12	175	555	800	4.6	1
VRH32	4.8	M33	62	38	71.5	50	370	60	M27	12	220	700	970	8.5	1
VRH38	6	M39	79	45	83.5	60.3	400	75	M33	16	230	780	1,060	15	1
VRH45	8.5	M45	94	50	86	76	400	85	M39	16	235	800	1,050	21	1
VRH50	11	M52	98	58	97.5	76	400	92	M45	16	240	825	1,050	24	1

Blueprint

