

## Electric-hydraulic lifting tables 400V

### Product information



For installation, repairs, packaging etc. Operating voltage 3-phase /380-400 V/50 Hz. Control device (cable) with lifting and lowering functions, as well as emergency stop. Equipped with a protection frame, which prevents the table from lowering, if something gets in between the plates. Electromagnetic valve, the table can not be lowered (it will stop), if a hose breaks. Delivered completely assembled without plug.

**Features:** Lifting times 1/2t: 20 sek | 4t: 40 sek

**Material:** Steel

**Marking:** According to standard, CE-marked

**Finish:** Painted, yellow

**Standard:** EN 1570

Part Code	Max load kg	L mm	B mm	L1 mm	B1 mm	H mm	Weight kg	Delivery time
NOSP1000H	1,000	1,300	820	1,266	680	205 - 990	160	0
NOSP2000H	2,000	1,600	1,000	1,255	785	230 - 1000	268	0
NOSP4000H	4,000	2,000	1,200	1,600	930	240 - 1050	405	0

Technical data

SPARE PARTS

Spare part (product code)	Description	Suitable for lift table (product code/-s)
NOSPHKAPULA	Hand control switch   Incl. cable and plug	NOSP1000H, NOSP2000H, NOSP4000H
NOSPBOX2	Electric control box/unit   New type, with steel connectors	NOSP1000H, NOSP2000H, NOSP4000H

Note: Suitable for lifting tables manufactured after (year) 2013

Also other spare parts available with a delivery time, ask our sales for more information

## Blueprint

