

Steel wire rope sling - type 1

Product information



- The steel wire rope is equipped with pressing buckles, master ring and a latch hook
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

[... Read more](#)

Features: Steel core


Rope construction: 6X36-IWRC

Marking: CE-marked

Finish: Rope, hot dip galvanized | Components, painted yellow

Steel wire rope sling - type 1

Blueprint



Technical data / Spare Parts

Part code	Diameter mm	WLL ton
TER10601	6	0.35
TER10801	8	0.7
TER11001	10	1.05
TER11201	12	1.55
TER11401	14	2.12
TER11601	16	2.7
TER11801	18	3.4
TER12002	20	4.35
TER12202	22	5.2
TER12402	24	6.3
TER12602	26	7.2
TER12802	28	8.4
TER13002	30	9.7
TER13202	32	11
TER13603	36	14
TER14003	40	17
TER14403	44	21
TER14803	48	25
TER15203	52	29
TER15603	56	33.5
TER16003	60	39

Steel wire rope sling - type 1

Working load limits (WLL)

Rope Ø	WLL tons		
	Straight lift	Choke hitch	Basket hitch
6	0,35	0,28	0,7
8	0,7	0,55	1,4
10	1,05	0,85	2,1
12	1,55	1,2	3,1
14	2,12	1,7	4,2
16	2,7	2,2	5,4
18	3,4	2,7	6,8
20	4,35	3,4	8,7
22	5,2	4,1	10,4
24	6,3	5	12,6
26	7,2	5,8	14,4
28	8,4	6,7	16,8
32	11	8,8	22
36	14	11,2	28
40	17	13,6	34
44	21	16,8	42
48	25	20	50
52	29	23,2	58
56	33,5	26,8	67
60	39	31,2	78