



Steel wire rope sling - type 6

Product information

- The steel wire rope is equipped with pressing buckles and loop ends
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Features: Steel core

Rope construction: 6X36-IWRC

Marking: CE-marked

Finish: hot dip galvanized

Part code	Rope diameter mm	WLL ton	WLL Straight Lift ton	Eye diameter mm	Delivery time days
TER60601	6	0.35	-	100	14
TER60801	8	0.7	0.7	150	14
TER61001	10	1.05	1.05	150	14
TER61201	12	1.55	1.55	200	14
TER61401	14	2.12	2.12	200	14
TER61601	16	2.7	2.7	250	14
TER61801	18	3.4	3.4	250	14
TER62002	20	4.35	4.35	300	14
TER62202	22	5.2	5.2	300	14
TER62402	24	6.3	6.3	350	14
TER62602	26	7.2	7.2	350	14
TER62802	28	8.4	8.4	400	14
TER63002	30	9.7	9.7	400	14
TER63202	32	11	11	400	14
TER63603	36	14	14	-	14
TER64003	40	17	17	-	14
TER64403	44	21	21	-	14
TER64803	48	25	25	-	14
TER65203	52	29	29	-	14
TER65603	56	33.5	33.5	-	14
TER66003	60	39	39	-	14

Technical data / Spare Parts

Working load limits (WLL)

Rope	WLL tons		
∅	<input type="text"/>	<input type="text"/>	<input type="text"/>
mm	Straight lift	Choke hitch	Basket hitch
6	0,35	0,28	0,7
8	0,7	0,55	1,4
10	1,05	0,85	2,1
12	1,55	1,2	3,1
14	2,12	1,7	4,2
16	2,7	2,2	5,4
18	3,4	2,7	6,8
20	4,35	3,4	8,7
22	5,2	4,1	10,4
24	6,3	5	12,6
26	7,2	5,8	14,4
28	8,4	6,7	16,8
32	11	8,8	22
36	14	11,2	28
40	17	13,6	34
44	21	16,8	42

48	25	20	50
52	29	23,2	58
56	33,5	26,8	67
60	39	31,2	78

Blueprint

