Steel wire rope sling - type 7

Product information



- The steel wire rope is equipped with pressing buckles and loop/thimble ends
- wire rope strength 1770 N / mm2
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

... *Read more*

Features: Steel core
Rope construction: 6X36-IWRC
Marking: CE-mark
Finish: hot dip galvanized

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Steel wire rope sling - type 7

Blueprint



Technical data / Spare Parts

Part code	Rope diameter mm	WLL ton
TER70601	6	0.35
TER70801	8	0.7
TER71001	10	1.05
TER71201	12	1.55
TER71401	14	2.12
TER71601	16	2.7
TER71801	18	3.4
TER72002	20	4.35
TER72202	22	5.2
TER72402	24	6.3
TER72602	26	7.2
TER72802	28	8.4
TER73002	30	9.7
TER73202	32	11
TER73603	36	14
TER74003	40	17
TER74403	44	21
TER74803	48	25
TER75203	52	29
TER75603	56	33.5
TER76003	60	39

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Steel wire rope sling - type 7

Working load limits (WLL)

Rope	WLL tons		
Ø			
mm	Straight lift	Choke hitch	Basket hitch
6	0,35	0,28	0,7
8	0,7	0,55	1,4
10	1,05	0,85	2,1
12	1,55	1,2	3,1
14	2,12	1,7	4,2
16	2,7	2,2	5,4
18	3,4	2,7	6,8
20	4,35	3,4	8,7
22	5,2	4,1	10,4
24	6,3	5	12,6
26	7,2	5,8	14,4
28	8,4	6,7	16,8
32	11	8,8	22
36	14	11,2	28
40	17	13,6	34
44	21	16,8	42
48	25	20	50
52	29	23,2	58
56	33,5	26,8	67
60	39	31,2	78

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved