



Steel wire rope sling - type 7

Product information

- The steel wire rope is equipped with pressing buckles and loop/thimble ends
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Features: Steel core

Rope construction: 6X36-IWRC

Marking: CE-marked

Finish: hot dip galvanized

Part code	Rope diameter mm	WLL ton	Delivery time days
TER70601	6	0.35	14
TER70801	8	0.7	14
TER71001	10	1.05	14
TER71201	12	1.55	14
TER71401	14	2.12	14
TER71601	16	2.7	14
TER71801	18	3.4	14
TER72002	20	4.35	14
TER72202	22	5.2	14
TER72402	24	6.3	14
TER72602	26	7.2	14
TER72802	28	8.4	14
TER73002	30	9.7	14
TER73202	32	11	14
TER73603	36	14	14
TER74003	40	17	14
TER74403	44	21	14
TER74803	48	25	14
TER75203	52	29	14
TER75603	56	33.5	14
TER76003	60	39	14

Technical data / Spare Parts

Working load limits (WLL)

Rope	WLL tons		
∅	<input type="text"/>	<input type="text"/>	<input type="text"/>
mm	Straight lift	Choke hitch	Basket hitch
6	0,35	0,28	0,7
8	0,7	0,55	1,4
10	1,05	0,85	2,1
12	1,55	1,2	3,1
14	2,12	1,7	4,2
16	2,7	2,2	5,4
18	3,4	2,7	6,8
20	4,35	3,4	8,7
22	5,2	4,1	10,4
24	6,3	5	12,6
26	7,2	5,8	14,4
28	8,4	6,7	16,8
32	11	8,8	22
36	14	11,2	28
40	17	13,6	34
44	21	16,8	42

48	25	20	50
52	29	23,2	58
56	33,5	26,8	67
60	39	31,2	78

Blueprint

