



Steel wire rope sling - type 10

Product information

- endless steel wire rope sling is equipped with pressing buckle
- wire rope strength 1770 N / mm²
- also available with spliced connections, larger workloads and special ends, ask more about our sales

Note! The last two digits of the product code indicate the length (L), so tell the length of the sling when ordering.

Features: Steel core

Rope construction: 6X36-IWRC

Marking: CE-marked

Finish: hot dip galvanized

Part code	Rope diameter mm	WLL	Delivery time days
TER100601	6	0.7	0
TER100801	8	1.4	0
TER101001	10	2.1	0
TER101201	12	3.1	0
TER101401	14	4.24	0
TER101601	16	5.4	0
TER101801	18	6.8	0
TER102002	20	8.7	0
TER102202	22	10.4	0
TER102402	24	12.6	0
TER102602	26	14.4	0
TER102802	28	16.8	0
TER103002	30	19.4	0
TER103202	32	22	0
TER103603	36	28	0
TER104003	40	34	0
TER104403	44	42	0
TER104803	48	50	0
TER105203	52	58	0
TER105603	56	67	0
TER106003	60	78	0

Technical data / Spare Parts

Working load limits (WLL)

Rope	WLL tons		
Ø	<input type="text"/>	<input type="text"/>	<input type="text"/>
mm	Straight lift	Choke hitch	Basket hitch
6	0,7	0,56	1,4
8	1,4	1,12	2,8
10	2,1	1,68	

Blueprint

