



## Lifting Eye Theipa Point - F

### Product information

The eyes can be loaded with working load limit in all directions. All the eyes are pivoted to avoid breakage in the eyes, which also make it possible to fold it aside when it is not in use. Furthermore it has a ball beared sviwel which makes the lifting eye to always stand in the correct direction to the load.

#### The advantages:

- The stamped WLL applies to the kind of attachment by 90°.
- Bolts of the quality class 10.9 crack-tested are permitted as connecting elements
- **Different threaded versions and lengths can be supplied on request.**

**Material:** Eye and swivel of alloy








**Marking:** WLL.

**Finish:** Painted.

**Safety factor:** 4:1

Part code	Code	WLL ton	Thread mm	Tightening torque Nm	Pitch DIN 13	a mm	Ø b	b i	d mm	e mm	g mm	SW mm	t mm	t1 mm	Ø mm	Weight kg	Delivery time days
NS10KL1205P	TP-F 0.5	0.5	M 12	15-40	1.75	45	36.5	32	M 12	15	73	34	66	55	13	0.61	17
NS10KL1610P	TP-F 1	1	M 16	45-130	2	52	36.5	32	M 16	20	80	34	73	55	13	0.65	17
NS10KL2017P	TP-F 1.7	1.7	M 20	100-170	2.5	66	52	34	M 20	25	106	46	95	70	16	1.5	17
NS10KL242P	TP-F 2.1	2.1	M 24	190-280	3	80	57	45	M 24	30	120	50	108	85	18	2.12	17
NS10KL3032P	TP-F 3.2	3.2	M 30	230-400	3.5	94	70	46	M 30	40	148	65	131	86	20	3.7	17
NS10KL365P	TP-F 5	5	M 36	270-600	4	107	80	60	M 36	45	164	75	145	115	23	5.75	1

Technical data / Spare Parts

Kind of attachment									
Number of pieces		1	1	2	2	2	2	3 o. 4	3 o. 4
Inclination angle		0°	90°	0°	90°	0°-45°	45°-60°	0°-45°	45°-60°
		WLL	WLL	WLL	WLL	WLL	WLL	WLL	WLL
Code	Thread version	t	t	t	t	t	t	t	t
TP-F 0,5	M 12 x 15	1,4	0,5	2,8	1,0	0,7	0,5	1,0	0,75
TP-F 1	M 16 x 20	2,8	1,0	5,6	2,0	1,4	1,0	2,12	1,5
TP-F 1,7	M 20 x 25	5,0	1,7	10,0	3,4	2,4	1,7	3,55	2,5
TP-F 2,1	M 24 x 30	8,0	2,1	16,0	4,0	2,8	2,1	4,25	3,15
TP-F 3,2	M 30 x 40	12,0	3,2	24,0	6,4	4,25	3,15	6,7	4,75
TP-F 5	M 36 x 45	15,0	5,0	30,0	10,0	6,7	5,0	10,0	7,5

Blueprint

