# Insulated Swivels 8-123

## Product information



Individually tested to resist 1500 Volts insulated with Test Certificate. Design for protection of overhead crane during welding operations on suspended loads.

... *Read more*

**Material:** Quenched and tempered alloy steel.
**Marking:** According to standard, CE-mark
**Standard:** EN 1677-1


**Safety factor:** 4:1
**Grade:** 8

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

# Insulated Swivels 8-123

## Blueprint




## Technical data / Spare Parts

| Part code | Chain diameter mm | WLL ton | A mm | D mm | L mm | Weight kg |
|---|---|---|---|---|---|---|
| LEIK78LL | 7-8 | 2 | 18 | 9 | 131 | 0.7 |
| LEIK10LL | 10 | 3.15 | 25 | 11 | 162 | 1.5 |
| LEIK13LL | 13 | 5.3 | 30 | 16 | 214 | 3.2 |
| LEIK16LL | 16 | 8 | 36 | 19 | 243 | 5.4 |
| LEIK20LL | 18-20 | 12.5 | 42 | 22 | 285 | 9 |

**Haklift Oy**
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved