Spur Gear Hand Winch TL150 Painted

Product information

This small compact hand-operated winch weighing only 4 kg excels because of its high speed. Its speed and size make it well suited to smaller jobs.

- robust and safe winch suitable for lifting and pulling
- Load pressure brake with double ratchet system for safe stable hold of the load in any position
- wire rope outlet upwards
- adjustable crank
- suitable for wall mounting
- 1 layer of paint

Options:

- zinc-plated finish 6 - 8 micron (EV)
- 2 layers of paint (2L)
- ATEX certified zone 2 and 22 (EX)
- CE II 3G Ex IIC T4 Gc, -20°C<T amb <+70°C
  CE II 3D Ex IIIC T135°C Dc, -20°C<T amb <+70°C

... *Read more*

Material: Steel
Marking: According to standard, CE-marked
Temperature range: -20°C up to +70°C
Finish: Painted, grey
Standard: EN 13157
Note: The cable must be ordered separately, ask for more information about our sales

Safety factor: 4:1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© October 2026 - All Rights Reserved

Spur Gear Hand Winch TL150 Painted

Blueprint



Technical data / Spare Parts

Part code	Code	WLL ton	Rope Ø mm	Rope capacity m	Capacity 1st layer kg	Capacity top layer kg	Weight kg
TL150	TL150	0.15	4	13.1	150	67	4

Haklift Oy
sales@haklift.com
+358 2 511 5511

© October 2026 - All Rights Reserved