

## Master Link MT

---

### Product information



Designed for use with chain or wire rope. For 3- and 4-leg slings.

... [Read more](#)

---

**Material:** Quenched and tempered alloy steel grade 10.

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677


**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

# Master Link MT

## Blueprint



## Technical data / Spare Parts

Part code	Code	WLL ton	L1mm mm	L mm	E mm	D, mm	lmm mm	e mm mm	dmm mm	Weight kg
NRLIA1006MT	MT-6-10	3.5	285	160	90	19	120	60	13	2
NRLIA1008MT	MT-8-10	5.2	300	160	95	22	140	80	17	3
NRLIA1010MT	MT-10-10	11.5	360	200	120	30	160	95	22	6.4
NRLIA1013MT	MT-13-10	17	440	250	150	40	190	110	28	14.2
NRLIA1016MT	MT-16-10	28	500	300	200	50	200	120	32	23
NRLIA1020MT	MT-20-10	35	550	300	200	55	250	150	40	31.5
NRLIA1022MT	MT-22-10	53	610	350	200	60	260	140	45	46
NRLIA1026MT	MT-26-10	70	730	450	250	70	280	160	50	71
NRLIA1032MT	MT-32-10	90	730	450	260	80	280	160	55	91