Master Link Hybrid MFH

Product information



Designed for crane hooks DIN 15401 and 15402. Designed for use with CL, CLD, CG and CGD. 3- and 4-leg chain slings require CLD / CGD.

... *Read more*

Material: Quenched and tempered alloy steel grade 10.
Marking: According to standard, code and grade.
Finish: Painted.
Standard: EN 1677
Warning: Not to be heat treated.

Safety factor: 5:1
Grade: 10

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Master Link Hybrid MFH

Blueprint



Technical data / Spare Parts

Part code	Code	WLL ton	For chain, 1-leg mm	For chain, 2-leg mm	For chain, 3-4-leg mm	For crane hooks	D mm	E mm	L mm	Weight kg
NORA101310MFH	MFH-1310-10	7.5	13	10	8	12	22	125	230	2.1
NORA101613MFH	MFH-1613-10	10	16	13	10	12	28	135	250	3.7
NORA102016MFH	MFH-2016-10	17	20	16	13	16	32	135	280	5.3
NORA102220MFH	MFH-2220-10	28	26	20	16	25	40	175	320	9.7
NORA102220MFHW	MFHW-2220-10	28	26	20	16	50	40	225	355	11.1

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved