



Coupling Link Gunnebo, G Grabiq

Product information

For use with master link and eye hook.

Material: Quenched and tempered alloy steel.

Marking: According to standard, code and grade.

Finish: Painted.

Standard: EN 1677

Warning: Not to be heat treated.

Safety factor: 4:1

Grade: 10

Part code	Code	Chain diameter mm	WLL ton	A,	B,	C,	F,	L	Weight kg	Delivery time days
LLA1006G	G-6-10	6	1.5	8	15	16	7	45	0.1	14
LLA1007G	G-7-10	7	2	11	18	22	9	56	0.2	14
LLA1008G	G-8-10	8	2.6	11	18	22	9	56	0.2	14
LLA1010G	G-10-10	10	4	13	25	26	12	68	0.3	14
LLA1013G	G-13-10	13	6.8	17	29	33	15	89	0.7	14
LLA1016G	G-16-10	16	10.3	20	36	40	19	106	1.4	14
LLA1020G	G-20-10	20	16	26	43	44	23	125	2.2	14
LLA1022G	G-22-10	22	20	28	50	59	26	152	3.6	14
LLA1026G	G-26-10	26	27.3	34	58	61	32	161	5.7	14
LLA1032G	G-32-10	32	40	40	70	77	38	200	9.5	14

Blueprint

