



Grab Hook OG

Product information

Eye shortening hook. No reduction of working load limit, thanks to supporting lugs on either side of hook to prevent chain link deformation.

Material: Quenched and tempered alloy steel.

Marking: According to standard, code and grade.

Finish: Painted.

Standard: EN 1677

Warning: Not to be heat treated.

Safety factor: 4:1

Grade: 10

| Part code | Code | WLL ton | B, | E, | F, | L | Weight kg | Delivery time days |
|------------|-----------|---------|----|----|----|-----|-----------|--------------------|
| LYKA1078OG | OG-7/8-10 | 2.6 | 10 | 17 | 10 | 65 | 0.3 | 14 |
| LYKA1010OG | OG-10-10 | 4 | 12 | 20 | 12 | 85 | 0.7 | 14 |
| LYKA1013OG | OG-13-10 | 6.8 | 16 | 26 | 16 | 104 | 1.6 | 14 |
| LYKA1016OG | OG-16-10 | 10.3 | 20 | 32 | 19 | 131 | 2.8 | 14 |
| LYKA1020OG | OG-20-10 | 16 | 26 | 41 | 23 | 167 | 6.1 | 14 |
| LYKA1022OG | OG-22-10 | 20 | 26 | 46 | 26 | 187 | 7.75 | 14 |
| LYKA1026OG | OG-26-10 | 27.3 | 32 | 55 | 38 | 228 | 14 | 14 |
| LYKA1032OG | OG-32-10 | 40 | 40 | 50 | 27 | 229 | 20.7 | 14 |

Blueprint

