



## Swivel Safety Hook BKL

### Product information

Swivel safety hook BKL, with recessed trigger.

**Material:** Quenched and tempered alloy steel

**Marking:** According to standard, code and grade.

**Finish:** Painted.

**Standard:** EN 1677

**Warning:** Not to be heat treated.

**Safety factor:** 4:1

**Grade:** 10

| Part code    | Code       | WLL ton | A mm | B mm | C mm | E mm | G mm | H mm | L   | Weight kg | Delivery time days |
|--------------|------------|---------|------|------|------|------|------|------|-----|-----------|--------------------|
| VAKAL1006BKL | BKL-6-10   | 1.5     | 11   | 29   | 23   | 33   | 15   | 21   | 149 | 0.7       | 14                 |
| VAKAL1078BKL | BKL-7/8-10 | 2.6     | 12   | 37   | 27   | 38   | 17   | 26   | 183 | 1.2       | 14                 |
| VAKAL1010BKL | BKL-10-10  | 4       | 15   | 45   | 37   | 44   | 21   | 31   | 218 | 2         | 14                 |
| VAKAL1013BKL | BKL-13-10  | 6.8     | 19   | 55   | 49   | 48   | 30   | 40   | 282 | 4         | 14                 |
| VAKAL1016BKL | BKL-16-10  | 10.3    | 25   | 62   | 65   | 61   | 37   | 50   | 341 | 7.2       | 14                 |

# Blueprint

