Chain Grabiq-short Link Grade 10

Product information



General: Chain for lifting. Has a maximum service temperature of 200°C ... *Read more*

Material: Quenched and tempered alloy steel.
Marking: According to standard, Code and grade.
Standard: EN 818-2
Warning: Not to be heat treated!


Safety factor: 4:1
Grade: 10

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Chain Grabiq-short Link Grade 10

Blueprint



Technical data / Spare Parts

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Length m	P mm	d mm	w1mm mm	Weight kg
NK1006G	6	1.5	58.9	200	18	6	8.5	0.8
NK1007G	7	1.95	77	200	21	7	10	1.1
NK1008G	8	2.6	102	200	24	8	11	1.4
NK1010G	10	4	158	100	30	10	14	2.3
NK1013G	13	6.8	268	100	39	13	18.8	4
NK1016G	16	10.3	402	100	48	16	21.9	5.6
NK1020G	20	16	630	50	60	20	27	9.4
NK1022G	22	20	785	50	66	22	29	11.9
NK1026G	26	27	1,062	50	78	26	35	16.4

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved