

Round Sling Extreema® XS

Product information



The Extreema® XS sling is a compact high-strength round sling designed for lifting operations in confined or restricted spaces. It is used where traditional slings are too bulky or require larger hardware. Manufactured from HMPE, it combines high load capacity with a small diameter, enabling efficient and controlled lifting in tight environments.

WLL range: 3 – 20t

EWL range: 0,5m – 16m, (15t/20t can be made up to 65m)

When to choose this product

Best for:

- Lifting in confined spaces with limited clearance
- Applications requiring compatibility with standard shackles

Product benefits

- Compact diameter enables lifting in restricted or hard-to-reach areas
- D:d ratio 1:1 allows use with standard bow shackles
- HMPE construction provides high strength with low weight
- Lightweight design simplifies transport, handling, and storage
- Seamless sleeve supports durability and extended service life

... [Read more](#)

Material: HMPE

Marking: According to standard, CE-marked

Temperature range: -40°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

Round Sling Extreema® XS

Technical data / Spare Parts

Part code	WLL ton	EWL m	Colour
PAR301XS	3	0.5	Yellow
PAR302XS	3	1	Yellow
PAR303XS	3	1.5	Yellow
PAR304XS	3	2	Yellow
PAR305XS	3	2.5	Yellow
PAR306XS	3	3	Yellow
PAR308XS	3	4	Yellow
PAR310XS	3	5	Yellow
PAR501XS	5	0.5	Red
PAR502XS	5	1	Red
PAR503XS	5	1.5	Red
PAR504XS	5	2	Red
PAR505XS	5	2.5	Red
PAR506XS	5	3	Red
PAR508XS	5	4	Red
PAR510XS	5	5	Red
PAR1003XS	10	1.5	Orange
PAR1004XS	10	2	Orange
PAR1006XS	10	3	Orange
PAR1008XS	10	4	Orange
PAR1010XS	10	5	Orange