



Round Sling Extreema® XS

Product information

The Extreema® XS sling is a compact high-strength round sling designed for lifting operations in confined or restricted spaces. It is used where traditional slings are too bulky or require larger hardware. Manufactured from HMPE, it combines high load capacity with a small diameter, enabling efficient and controlled lifting in tight environments.

WLL range: 3 – 20t

EWL range: 0,5m – 16m, (15t/20t can be made up to 65m)

When to choose this product

Best for:

- Lifting in confined spaces with limited clearance
- Applications requiring compatibility with standard shackles

Product benefits

- Compact diameter enables lifting in restricted or hard-to-reach areas
- D:d ratio 1:1 allows use with standard bow shackles
- HMPE construction provides high strength with low weight
- Lightweight design simplifies transport, handling, and storage
- Seamless sleeve supports durability and extended service life

Material: HMPE

Marking: According to standard, CE-marked

Temperature range: -40°C up to +70°C

Standard: EN 1492-2

except material

Safety factor: 7:1

Part code	WLL ton	EWL m	Colour	Delivery time days
PAR301XS	3	0.5	Yellow	14
PAR302XS	3	1	Yellow	14
PAR303XS	3	1.5	Yellow	14
PAR304XS	3	2	Yellow	14
PAR305XS	3	2.5	Yellow	14
PAR306XS	3	3	Yellow	1
PAR308XS	3	4	Yellow	14
PAR310XS	3	5	Yellow	14
PAR501XS	5	0.5	Red	14
PAR502XS	5	1	Red	14
PAR503XS	5	1.5	Red	14
PAR504XS	5	2	Red	1
PAR505XS	5	2.5	Red	14
PAR506XS	5	3	Red	14
PAR508XS	5	4	Red	14
PAR510XS	5	5	Red	14
PAR1003XS	10	1.5	Orange	14
PAR1004XS	10	2	Orange	14
PAR1006XS	10	3	Orange	1
PAR1008XS	10	4	Orange	14
PAR1010XS	10	5	Orange	14

Technical data / Spare Parts

Extreema® XS roundsling				
HMPE EXS				
WLL	SF	Core ø mm	Weight kg 3m EWL	p/m extra kg
3t	7	9	0,8	0,25
5t	7	14	1,35	0,43
10t	7	23	2	0,65
15t	7	31	3,5	1,15
20t	7	37	4,6	1,50