



## Lashing system 50 mm / LC 2500 daN / 10 m r-PET recycled material

### Product information



The lashing system is made from **recycled** high-strength polyester (r-PET) yarn, Cr6 free steel ratchets and hooks. Because the webbing is made from r-PET yarn, this product has a **42% CO<sub>2</sub> reduction\*** compared to the standard cargo securing lashing system.

This lashing system is part of Lifting Solution Group's Aspire range™. In November 2023, this product won the prestigious LEEA Sustainable Award.

- Strong and durable with LC 2500 daN and STF 350 daN
- Webbing has min. breaking strength of 7500 daN
- Blue webbing with 2500 daN print for easy identification
- Both the long part and short part carry blue identification labels
- Label gives information on STF and lashing capacity for different lashing connections
- Year/Month calendar printed on the label where latest inspection date can be marked or punched
- Cr6 free galvanization – better for health and environment
- Lashing system can be supplied with other lengths and other end fittings on request

\*A 3rd party climate LCA with a cradle-to-gate perspective according to ISO14067 has shown that our r-PET web lashings have 42% fewer CO<sub>2</sub> emissions than our standard product. This means that our products are not only better for the environment but also make a positive contribution to reducing CO<sub>2</sub> emissions.

**Material:** 100% polyester (PES) high tenacity multifilament made from r-PET (recycled PET), and Steel.

**Temperature range:** -40°C up to +120°C

**Warning:** Protect the lashings from sharp edges

Part code	LC daN	2xLC (daN)	Length m	Band width mm	Design	Fitting	Colour	Weight kg	Delivery time days
-----------	-----------	---------------	-------------	------------------	--------	---------	--------	--------------	-----------------------

SV3500102RPET	2,500	5,000	10	50	2-part	Wire hook double	Blue	2.75	10
---------------	-------	-------	----	----	--------	------------------	------	------	----