

## Electric Chain Hoist LIFTKET STAR ONE 030 125 - 1.000 kg

### Product information



Electric Chain Hoist Liftket STAR ONE impresses with its load-dependent speed control. Thanks to its speed ramp, it enables smooth acceleration and deceleration. STAR ONE can be easily connected to any single-phase grid with a voltage of 110 to 240 V and a frequency of 50 or 60 Hz. This wide compatibility enables universal use worldwide, regardless of regional power grid standards. This makes the device ideal for international applications and various locations.

#### Features:


- Single-phase grid
- Load-dependent lifting speeds
- Power supply 230 V, 1 phase, 50 Hz
- Up to 1.000 kg load capacity
- Standard lifting height 3 m
- 1.5m control cable
- Control pendant with emergency stop
- Protection class IP55
- Equipped with EASY CONNECT
- VFD control 24 V DC
- Upper/lower limit switches
- Starting and slowing down by speed ramp

... [Read more](#)

**Marking:** CE-marked

## Electric Chain Hoist LIFTKET STAR ONE 030 125 - 1.000 kg

### Blueprint



### Technical data / Spare Parts

Part code	Code	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Motor kW	Class ISO/FEM	Load chain mm	A mm	B mm	C mm	G mm	H mm	I mm	J mm	K mm	M mm	N mm	O mm	P mm	V mm	Weight kg
SKT125KV1S1	125/1-8	0.125	3	8	1	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	365	525	15	20	19	12	37	40	24	74	22
SKT250KV1S1	250/1-8	0.25	3	7	1	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	365	525	15	20	19	12	37	40	24	74	22
SKT500KV1S1	500/1-8	0.5	3	5	1	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	365	525	15	20	19	12	37	40	24	74	22
SKT1000KV2S1	1000/2-4	1	3	2,5	2	0.70/0.00	M4/ 1Am	5.2x15	221	235	220	428	540	19	22	24	12	37	40	24	74	26