



## Electric Chain Hoist LIFTKET STAR ONE 030 125 - 1.000 kg

### Product information

Electric Chain Hoist Liftket STAR ONE impresses with its load-dependent speed control. Thanks to its speed ramp, it enables smooth acceleration and deceleration. STAR ONE can be easily connected to any single-phase grid with a voltage of 110 to 240 V and a frequency of 50 or 60 Hz. This wide compatibility enables universal use worldwide, regardless of regional power grid standards. This makes the device ideal for international applications and various locations.

#### Features:

- Single-phase grid
- Load-dependent lifting speeds
- Power supply 230 V, 1 phase, 50 Hz
- Up to 1.000 kg load capacity
- Standard lifting height 3 m
- 1.5m control cable
- Control pendant with emergency stop
- Protection class IP55
- Equipped with EASY CONNECT
- VFD control 24 V DC
- Upper/lower limit switches
- Starting and slowing down by speed ramp

**Marking:** CE-marked

Part code	Code	WLL ton	Lifting height m	Lifting speed m/min	Number of falls	Motor kW	Class ISO/FEM	Load chain mm	A, B, C, G, H, I	J, K, M	N	O	P	V	Weight kg	Delivery time days
SKT125KV1S1	125/1-8	0.125	3	8	1	0.70/0.00	M4/ 1Am	5.2x15	221 235 220 365 525	15 20 19	12 37	40 24	74	22	35	
SKT250KV1S1	250/1-8	0.25	3	7	1	0.70/0.00	M4/ 1Am	5.2x15	221 235 220 365 525	15 20 19	12 37	40 24	74	22	35	
SKT500KV1S1	500/1-8	0.5	3	5	1	0.70/0.00	M4/ 1Am	5.2x15	221 235 220 365 525	15 20 19	12 37	40 24	74	22	35	
SKT1000KV2S1	1000/2-4	1	3	2,5	2	0.70/0.00	M4/ 1Am	5.2x15	221 235 220 428 540	19 22 24	12 37	40 24	74	26	35	

## Blueprint

