
Chain WOX Stainless Pewag - Short Link

Product information



Stainless steel lifting chain, electrically welded and stamped, guaranteed compatible with Connex CWI connectors.

Standard: Similar DIN 5687-1

The WOX chain is particularly suited for use in water and wastewater applications. It can also be used in connection with chemicals and food products; however, restrictions will apply.

... *Read more*

Material: 1.4404 (AISI 316L).
Marking: According to standard
Finish: Brightly polished.
Standard: EN 818-2


Safety factor: 4:1
Grade: 6

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Chain WOX Stainless Pewag - Short Link

Blueprint



Technical data / Spare Parts

Part code	Chain diameter mm	WLL ton	Min. breaking force kN	Model	b1 min. mm	b2 max. mm	dn mm	t mm	Weight kg/m
NKHK6	6	0.9	37.5	WOX 6-6	8	21.5	6	18	0.88
NKHK8	8	1.6	63	WOX 8-6	10.8	28.6	8	24	1.53
NKHK10	10	2.5	100	WOX 10-6	13.5	36	10	30	2.4
NKHK13	13	4.25	170	WOX 13-6	17.5	46.8	13	39	4.05

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved