Universal Surface-mounted Lashing Track

Product information



The surface-mounted universal lashing track provides a durable and versatile anchoring point for cargo securing in vans, trucks, trailers, and other transport equipment. The track is mounted directly onto the vehicle wall, or other structures, allowing for quick and straightforward installation without recessing. Its universal slot pattern enables flexible positioning of compatible lashing fittings and accessories along the entire length of the track. The zinc-plated steel construction, combined with integrated water drainage holes, offers excellent corrosion resistance and long service life in demanding operating conditions.

Best used for:

- Vehicle bodies, trailers and vans requiring adaptable cargo restraint systems.
- Installation where compatible Universal track fittings are used for securing or positioning loads.

Product benefits:

- Universal cargo restraint track for adaptable load securing configurations.
- Zinc-plated steel construction provides corrosion resistance for demanding transport environments.
- 2.3 mm steel profile offers a durable mounting solution.
- 25 mm hole pattern supports compatibility with suitable restraint accessories.
- Integrated water-draining holes help reduce moisture accumulation within the track.

... *Read more*

Material: Zinc plated steel

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Universal Surface-mounted Lashing Track

Blueprint



Technical data / Spare Parts

Part code	Length mm	Width mm	Thickness mm	Hole diameter mm	Depth mm
YKISKO3048	3,048	130	2.3	25	12.5

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved