Master Link MFX GrabiQ V2

Product information



Oversized master link MFX for 1-leg and 2-leg slings. Designed for use with chain, wire or synthetic rope. Applications with wire and synthetic rope generally require a 5:1 Design Factor.

... *Read more*

Material: Alloy Steel, Quenched & Tempered
Marking: According to standard, Code, grade, chain size, manufacturing ID
Standard: EN 1677-4 (+25% WLL) , AS 3775, AS 3776


Safety factor: 5:1
Grade: 10

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved

Master Link MFX GrabiQ V2

Blueprint



Technical data / Spare Parts

Part code	Code	WLL ton	L mm	E mm	D mm	Weight kg
NORA1008MFX	MFX-108-10 GrabiQ V2	5.4	340	180	22	2.8
NORA101310MFX	MFX-1310-10 GrabiQ V2	8.2	340	180	28	4.7
NORA101613MFX	MFX-1613-10 GrabiQ V2	13.6	340	180	32	6.2
NORA102016MFX	MFX-2016-10 GrabiQ V2	20.6	340	180	40	9.9

Haklift Oy
sales@haklift.com
+358 2 511 5511

© November 2026 - All Rights Reserved