

Lifting eye Screw

Product information

Lifting for all lifting directions.

WLL for vertical lifting is marked on the eye.

The depth of the threaded hole has to be minimum:

d = diameter of the lifting eye thread

- 1*d for steel
- 1,25*d for cast iron
- 2*d for aluminum alloys
- 2,5*d for aluminum magnesium alloys

Marking: According to standard, CE-marked
Standard: EN 1677-1

Safety factor: 4:1

Код товара	WLL ton	Size	Dia Eye mm	Thread pitch mm	D mm	L mm	K mm	Вес kg	Delivery time
NS8R06	0,4	M6	16	1	28	42	13	0,05	0
NS8R08	0,8	M8	20	1,25	39	51	15	0,06	0
NS8R10	1	M10	25	1,5	45	63	18	0,11	0
NS8R12	2	M12	30	1,75	54	75	22	0,18	0
NS8R14	3	M14	35	2	63	88	28	0,28	0
NS8R16	4	M16	35	2	63	88	28	0,28	0
NS8R20	6	M20	40	2,5	72	101	30	0,45	0
NS8R24	8	M24	50	3	90	128	38	0,87	0
NS8R30	12	M30	60	3,5	108	154	45	1,66	0
NS8R36	16	M36	70	4	126	183	55	2,65	0
NS8R42	24	M42	80	4,5	144	212	65	4,03	0
NS8R48	32	M48	90	5	166	238	70	6,38	0

Blueprint

