



Hand chain blocks

Product information

Haklift Chain Block is a hoist of high quality, it is durable and easy to operate using the ergonomic hand chain. The maximum workload is achieved with a fairly low manual force. The standard lifting heights are 3 m and 6 m. Other lifting heights are also available with fast delivery time from stock.

Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Compact, lightweight construction.
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- The unique surface treatment gives excellent corrosion protection and low operating volume
- Swivel hooks at both ends makes in line positioning easy
- · Hooks are designed to open at overload instead of breaking
- · Hooks fitted with heavy duty steel safety latches
- · Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection, HF -13,56 Mhz
- · Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available
- Can be supplied with overload protection (OLP) device.
- Other lifting heights are also available upon request
- · Length of the hand chain is always the same as the lifting height

Marking: According to standard, CE-marked Standard: EN 13157

Код товара	WLL ton	Lifting height m	Chain falls	Chain diam. mm	A mm	B mm	C mm	D mm	H mm	Bec kg	Delivery time
KTHA250	0,25	3	1	4 x 12	108	106	20	30	260	6,5	0
KTHA2506	0,25	6	1	4 x 12	108	106	20	30	260	7,55	0
KTHA500	0,5	3	1	5 x 15	130	128	22	34	280	9,8	0
KTHA5006	0,5	6	1	5 x 15	130	128	22	34	280	11,4	0
KTHA1000	1	3	1	6,3 x 19	150	142	26	39	330	13,3	0
KTHA10006	1	6	1	6,3 x 19	150	142	26	39	330	15,9	0
KTHA2000	2	3	1	8 x 24	185	175	35	49	385	22,1	0
KTHA20006	2	6	1	8 x 24	185	175	35	49	385	25,3	-
KTHA3000	3	3	2	7,1 x 21	220	158	37	50	510	27,3	0
KTHA30006	3	6	2	7,1 x 21	220	158	37	50	510	33,9	0
KTHA5000	5	3	2	9 x 27	255	183	43	60	615	42,4	0
KTHA50006	5	6	2	9 x 27	255	183	43	60	615	53,2	0
KTHA10000	10	6	4	9 x 27	360	183	47	65	820	115,4	0
KTHA20000	20	8	8	9 x 27	577	183	75	90	1 060	200	0

Blueprint

