



Push trolley

Product information

Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

Marking: According to standard, CE-marked

Standard: EN 13157

Safety factor: 4:1

Код товара	WLL ton	Beam width mm	Min. Radius Curve m	B mm	J mm	K mm	F mm	E mm	D mm	L mm	H mm	G mm	Bec kg	Delivery time
SIVA05H	0,5	55-220	0,5	285	198	158	12,5	40	3	55	80	25	5	-
SIVA05HL	0,5	55-305	0,5	385	198	158	12,5	40	3	55	80	25	5,4	-
SIVA10H	1	58-220	0,7	300	238	183	17	31	3	68	96	29	8,8	0
SIVA10HL	1	58-305	0,7	238	-	183	17	31	3	68	96	29	9,3	-
SIVA20H	2	66-220	0,9	300	277	208	20	31	3	80	110	36	14	0
SIVA20HL	2	66-305	0,9	405	277	208	20	31	3	80	110	36	14,8	-
SIVA30H	3	74-220	1,2	328	324	249	26	31	3	100	132	46	23	0
SIVA30HL	3	74-305	1,2	429	324	249	26	31	~3	100	132	46	24,1	-
SIVA50H	5	90-220	1	354	373	296,5	28	40	5	120	155	52	40	0
SIVA50HL	5	90-305	1	435	373	296,5	28	40	~5	120	155	52	41,1	-

Blueprint

