



## Eye sling hook with latch, grade 80

### Product information

Hook is equipped with spring loaded safety latch.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-2

**Safety factor:** 4:1

**Класс:** 8

| Код товара | WLL<br>ton | For chain Ø<br>mm | K<br>mm | E<br>mm | F<br>mm | R<br>mm | A mm | Bec<br>kg | Delivery time |
|------------|------------|-------------------|---------|---------|---------|---------|------|-----------|---------------|
| SALK6      | 1,12       | 6                 | 108     | 24      | 9       | 21      | 20   | 0,3       | 1             |
| SALK78     | 2          | 7/8               | 133     | 30      | 11      | 26      | 25   | 0,4       | 1             |
| SALK10     | 3,15       | 10                | 167     | 34      | 15      | 39      | 38   | 0,9       | 1             |
| SALK13     | 5,3        | 13                | 213     | 39      | 19      | 54      | 43   | 1,7       | 1             |
| SALK16     | 8          | 16                | 255     | 46      | 23      | 64      | 50   | 3,2       | 1             |
| SALK20     | 12,5       | 20                | 305     | 40      | 24      | 80      | 62   | 5,8       | 1             |
| SALK22     | 15         | 22                | 348     | 71      | 32      | 80      | 62   | 8,5       | 1             |
| SALK26     | 21,2       | 26                | 394     | 81      | 35      | 82      | 64   | 13        | 1             |
| SALK32     | 31,5       | 32                | 480     | 102     | 37      | 112     | 68   | 17        | 1             |
| SALK36     | 40         | 36                | n.530   | 109     | -       | -       | 72   | 32,3      | 14            |
| SALK40     | 50         | 40                | n.580   | 124     | -       | -       | 84   | 47        | 14            |

## Blueprint

