

## Lifting eye nut, grade 80



### Product information

Lifting for all lifting directions.

WLL for vertical lifting is marked on the eye.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

**Safety factor:** 4:1

| Код товара | WLL<br>ton | Size | Dia Eye<br>mm | Thread pitch<br>mm | D<br>mm | L<br>mm | Bec<br>kg | Delivery time |
|------------|------------|------|---------------|--------------------|---------|---------|-----------|---------------|
| NS8M06     | 0,4        | M6   | 20            | 1                  | 36      | 36      | 0,05      | 0             |
| NS8M08     | 0,8        | M8   | 20            | 1,25               | 36      | 36      | 0,05      | 0             |
| NS8M10     | 1          | M10  | 25            | 1,5                | 45      | 45      | 0,09      | 0             |
| NS8M12     | 2          | M12  | 30            | 1,75               | 54      | 53      | 0,16      | 0             |
| NS8M14     | 3          | M14  | 35            | 2                  | 63      | 62      | 0,24      | 0             |
| NS8M16     | 4          | M16  | 35            | 2                  | 63      | 62      | 0,24      | 0             |
| NS8M20     | 6          | M20  | 40            | 2,5                | 72      | 71      | 0,36      | 0             |
| NS8M24     | 8          | M24  | 50            | 3                  | 90      | 90      | 0,72      | 0             |
| NS8M30     | 12         | M30  | 60            | 3,5                | 108     | 109     | 1,32      | 0             |
| NS8M36     | 16         | M36  | 70            | 4                  | 126     | 128     | 2,08      | 0             |
| NS8M42     | 24         | M42  | 80            | 4,5                | 144     | 147     | 3,11      | 0             |
| NS8M48     | 32         | M48  | 90            | 5                  | 166     | 168     | 5,02      | 0             |

## Blueprint

