

## Swivel Eye Bolt Codipro SS SEB



### Product information



The stainless steel version of the swivel eye bolt, SS.SEb, is fitted with an automatic position recovery system for optimum orientation in the direction of the sling. Thanks to its stainless steel version, the swivel eye bolt can be used in humid, corrosive, chemical, maritime.

Tightening by Allen key.

Permits the hook to move parallel to the supporting face of the ring being drawn at 90°

From M12 to M24 as standard; for loads from 0.5 t to 2.5 t.

**Design:** Centered lifting ring with double articulation except for the SEb, swivel eyebolt 360°.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1

*except grade/WLL*

**Safety factor:** 5:1

Код товара	WLL ton	Thread	Torque Nm	Standard L1 mm	A mm	B mm	C mm	D mm	L1 mm	S mm	Bec kg	Delivery time
NS8R12SS.SEb	0,55	M 12 (x1,75)	15	21	38	45	90	80	21	8	0,8	0
NS8R16SS.SEb	1,2	M 16 (x2)	50	27	38	45	90	80	27	8	0,82	0
NS8R20SS.SEb	1,5	M 20 (x2,5)	100	30	38	45	90	80	30	8	0,84	0
NS8R24SS.SEb	2,5	M 24 (x3)	100	36	38	45	90	80	36	8	0,9	0

## Blueprint

