

## Swivel Eye Bolt Codipro SEB UP



### Product information

The SEB lifting ring is a single swivel ring. Equipped with 2 pins that always guide it perfectly in the direction of the sling. It is specially designed for lifting, including rotating loads.

#### Features:

- Gradup steel ring that has a rotating range of 360°.
- Swivelling under load
- Safe alternative to C15 DIN 580 eye bolts.
- Torque key adaptor available on request.

**Marking:** According to standard, CE-marked

**Standard:** EN 1677-1  
*except grade/WLL*

**Safety factor:** 5:1

| Код товара | WLL<br>ton | Thread       | Torque<br>Nm | A<br>mm | B<br>mm | C<br>mm | D<br>mm | L1<br>mm | S<br>mm | X<br>mm | Bec<br>kg | Delivery time |
|------------|------------|--------------|--------------|---------|---------|---------|---------|----------|---------|---------|-----------|---------------|
| NS8R08SEB  | 0,4        | M 8 (x1.25)  | 6            | 30      | 34      | 60      | 57      | 14       | 6       | 20      | 0,24      | -             |
| NS8R10SEB  | 0,5        | M 10 (x1.50) | 10           | 30      | 34      | 60      | 57      | 17       | 6       | 20      | 0,24      | 0             |
| NS8R12SEB  | 0,8        | M 12 (x1.75) | 15           | 30      | 34      | 60      | 57      | 21       | 6       | 20      | 0,24      | 0             |
| NS8R16SEB  | 1,4        | M 16 (x2)    | 50           | 38      | 45      | 88      | 80      | 27       | 8       | 35      | 0,8       | -             |
| NS8R20SEB  | 2          | M 20 (x2.5)  | 100          | 38      | 45      | 88      | 80      | 30       | 8       | 35      | 0,8       | 0             |
| NS8R24SEB  | 3,2        | M 24 (x3)    | 160          | 38      | 45      | 88      | 80      | 36       | 14      | 35      | 0,8       | -             |
| NS8R30SEB  | 5,5        | M 30 (x3.5)  | 250          | 58      | 70      | 115     | 106     | 45       | 14      | 50      | 2,7       | -             |
| NS8R36SEB  | 9          | M 36 (x4)    | 320          | 83      | 94      | 168     | 155     | 54       | 14      | 70      | 7         | -             |

Blueprint

