



Lifting eye screw with swivel, grade 80

Product information

Lifting screw with swivel for all lifting directions. Also available with longer 120 mm thread.

Marking: According to standard, CE-marked

Standard: EN 1677-1

Safety factor: 4:1

Код товара	WLL ton	Thread mm	Thread length mm	diameter eye inside mm	Ø of eye mm	Thread pitch mm	b mm	g mm	t mm	Bec kg	Delivery time
NS8KL1003	0,45	M10	18	55x30	14	1,5	36	51	41	0,43	0
NS8KL1205	0,5	M12	18	55x30	14	1,75	36	51	41	0,44	0
NS8KL161	1,1	M16	20	55x30	14	2	36	52	42	0,46	0
NS8KL161120	1,1	M16	120	55x30	14	2	36	52	42	0,46	0
NS8KL202	2	M20	30	70x34	16	2,5	50	68	56	0,96	0
NS8KL202120	2	M20	120	70x34	16	2,5	50	68	56	0,96	0
NS8KL243120	3,2	M24	120	85x37	18	3	57	78	65,5	1,45	0
NS8KL2432	3,2	M24	40	85x37	18	3	57	78	65,5	1,45	0
NS8KL305120	5,3	M30	120	85x37	20	3,5	66	97	80,5	2,17	0
NS8KL3053	5,3	M30	35	85x37	20	3,5	66	97	80,5	2,17	0
NS8KL308	8	M30	35	115x50	22	3,5	80	112	92	3,57	0
NS8KL308120	8	M30	120	115x50	22	3,5	80	112	92	3,57	0
NS8KL368	8	M36	50	115x50	22	4	80	109	89,5	4,17	0
NS8KL368120	8	M36	120	115x50	22	4	80	109	89,5	4,17	0
NS8KL4210	10	M42	50	115x50	25	4,5	80	109	89,5	3,67	0
NS8KL4810	10	M48	50	115x50	25	5	80	109	89,5	4,02	0
NS8KL4510	10	M45	60	115x50	25	4,5	80	109	89,5	4,17	0
NS8KL5615	15	M56	84	152x70	32	5,5	117	310	280	11,6	0
NS8KL6415	15	M64	95	152x70	32	6	117	310	280	12,6	0

Blueprint

