



## Bow Shackles with Screw Collar Pin G-4161

### Product information

Bow shackles with screw pin

**Certification:** This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

**Standard:** EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 2, Grade A.

**Marking:** According to standard, CE-marked

**Standard:** EN 13889

**Safety factor:** 6:1

**Класс:** 6

| Код товара | WLL<br>ton | A<br>mm | B<br>mm | C<br>mm | D<br>mm | e<br>mm | f<br>mm | g<br>mm | h<br>mm | i<br>mm | j<br>mm | Вес<br>kg | Delivery time |
|------------|------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|-----------|---------------|
| SAK03P     | 0,33       | 5       | 6       | 12      | 5       | 9,5     | 22      | 16      | 36      | 29,5    | 26      | 0,02      | 0             |
| SAK05P     | 0,5        | 7       | 8       | 16,5    | 7       | 12      | 29      | 20      | 48,5    | 38      | 34      | 0,05      | 0             |
| SAK07P     | 0,75       | 9       | 10      | 20      | 9       | 13,5    | 32      | 22      | 56      | 46,5    | 40      | 0,1       | 0             |
| SAK10P     | 1          | 10      | 11      | 22,5    | 10      | 17      | 36,5    | 26      | 63,5    | 54      | 46      | 0,14      | 0             |
| SAK15P     | 1,5        | 11      | 13      | 26,5    | 11      | 19      | 43      | 29      | 74      | 59,5    | 51      | 0,19      | 0             |
| SAK20P     | 2          | 13,5    | 16      | 34      | 13      | 22      | 51      | 32      | 89      | 73      | 58      | 0,36      | 0             |
| SAK32P     | 3,25       | 16      | 19      | 40      | 16      | 27      | 64      | 43      | 110     | 89      | 75      | 0,63      | 0             |
| SAK47P     | 4,75       | 19      | 22      | 46      | 19      | 31      | 76      | 51      | 129     | 103     | 89      | 1,01      | 0             |
| SAK65P     | 6,5        | 22      | 25      | 52      | 22      | 36      | 83      | 58      | 144     | 119     | 102     | 1,5       | 0             |
| SAK85P     | 8,5        | 25      | 28      | 59      | 25      | 43      | 95      | 68      | 164     | 137     | 118     | 2,21      | 0             |
| SAK95P     | 9,5        | 28      | 32      | 66      | 28      | 47      | 108     | 75      | 185     | 153     | 131     | 3,16      | 0             |
| SAK120P    | 12         | 32      | 35      | 72      | 32      | 51      | 115     | 83      | 201     | 170     | 147     | 4,31      | 0             |
| SAK135P    | 13,5       | 35      | 38      | 80      | 35      | 57      | 133     | 92      | 227     | 186     | 162     | 5,55      | 0             |
| SAK170P    | 17         | 38      | 42      | 88      | 38      | 60      | 146     | 99      | 249     | 203     | 175     | 7,43      | 0             |
| SAK250P    | 25         | 45      | 50      | 103     | 45      | 74      | 178     | 126     | 300     | 243     | 216     | 12,84     | 0             |
| SAK350P    | 35         | 50      | 57      | 111     | 50      | 83      | 197     | 138     | 331     | 272     | 238     | 18,15     | 0             |
| SAK425P    | 42,5       | 57      | 65      | 130     | 57      | 95      | 222     | 160     | 377     | 310     | 274     | 26,29     | -             |
| SAK550P    | 55         | 65      | 70      | 145     | 65      | 105     | 260     | 180     | 433     | 344     | 310     | 37,6      | -             |

Blueprint

