



Dee Shackles with Screw Collar Pin G-4151

Product information

Dee shackle with screw collar pin.

Certification: This product can be supplied with a works certificate, 3.1 material certificate, manufacturer test certificate, EC Declaration of Conformity. All shackles starting from 2 t can be supplied with DNV 2.7-1 certificate.

Standard: EN 13889 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVB Class 2, Grade A.

Marking: According to standard, CE-marked

Standard: EN 13889

Safety factor: 6:1

Класс: 6

Код товара	WLL ton	A mm	B mm	C mm	D mm	e mm	f mm	g mm	h mm	Bec kg	Delivery time
SAK03S	0,33	5	6	12	5	9,5	19	33	29,5	0,02	0
SAK05S	0,5	7	8	16,5	7	12	22	41,5	38	0,05	0
SAK07S	0,75	9	10	20	9	13,5	26	50	46,5	0,09	0
SAK10S	1	10	11	22,5	10	17	32	59	54	0,14	0
SAK15S	1,5	11	13	26,5	11	19	37	68	59,5	0,19	0
SAK20S	2	13,5	16	34	13	22	43	81	73	0,32	0
SAK32S	3,25	16	19	40	16	27	51	97	89	0,54	0
SAK47S	4,75	19	22	46	19	31	59	112	103	0,87	0
SAK65S	6,5	22	25	52	22	36	73	134	119	1,34	0
SAK85S	8,5	25	28	59	25	43	85	154	137	2,08	0
SAK95S	9,5	28	32	66	28	47	90	167	153	2,77	0
SAK120S	12	32	35	72	32	51	94	180	170	3,72	-
SAK135S	13,5	35	38	80	35	57	115	209	186	5,14	-
SAK170S	17	38	42	88	38	60	127	230	203	6,85	-
SAK250S	25	45	50	103	45	74	149	271	243	11,45	0
SAK350S	35	50	57	111	50	83	171	305	272	16,86	-
SAK425S	42,5	57	65	130	57	95	190	345	310	24,61	-
SAK550S	55	65	70	145	65	105	203	376	344	32,65	-

Blueprint

