

Shackles, SAE - bow model with locking

Product information

Shackles approved for lifting. Bow shackles are suitable for use when more than one attachment is to be made to the body (multi-leg systems), or to allow freedom of movement in the plane of the bow. Locking bolt shackles are recommended for long-term and permanent installations, or when there is a natural tendency for the pin to unscrew (rotate) in the application, or when the shackle cannot be observed under operation.

Marking: According to standard, CE-marked

Standard: US. FED. SPEC. RR-C-271F

Safety factor: 6:1



Код товара	WLL ton	Nominal size In.	A mm	B mm	C mm	D mm	E mm	F mm	G mm	H mm	N mm	Bec kg	Delivery time
SAK05PLBP	0,5	1/4	12	8	29	7	20	16	33	47	7	0,05	0
SAK07PLBP	0,75	5/16	14	10	31	8	22	19	38	53	8	0,1	0
SAK10PLBP	1	3/8	17	11	37	10	26	23	45	63	10	0,15	0
SAK15PLBP	1,5	7/16	19	13	43	11	30	27	52	74	11	0,22	0
SAK20PLBP	2	1/2	21	16	48	13	34	30	59	84	13	0,36	0
SAK32PLBP	3,25	5/8	27	19	61	16	43	38	75	106	18	0,76	0
SAK47PLBP	4,75	3/4	32	23	72	19	51	46	89	126	21	1,23	0
SAK65PLBP	6,5	7/8	37	26	84	23	58	53	102	148	25	1,79	0
SAK85PLBP	8,5	1	43	29	96	26	69	61	119	167	27	2,57	0
SAK95PLBP	9,5	1-1/8	46	32	108	29	74	69	131	190	32	3,75	0
SAK120PLBP	12	1-1/4	52	35	119	32	83	76	146	210	35	5,31	0
SAK135PLBP	13,5	1-3/8	57	38	133	35	92	84	162	233	38	7,18	0
SAK170PLBP	17	1-1/2	61	42	146	38	99	92	175	254	41	9,43	0
SAK250PLBP	25	1-3/4	73	51	178	45	127	106	225	313	57	15,4	0
SAK350PLBP	35	2	83	57	197	51	146	122	256	348	61	23,7	0
SAK550PLBP	55	2-1/2	105	70	267	67	184	145	327	453	80	44,61	0
SAK850PLBP	85	3	127	83	330	76	200	165	365	546	92	70	0
SAK1200PLBP	120	3-1/2	133	96	372	92	229	203	419	626	105	120	0
SAK1500PLBP	150	4	140	108	368	104	254	229	468	653	116	153	-

Blueprint

