

## Wedge Socket for Lifts

### Product information

Symmetrical Wedge Socket for stranded steel wire ropes according to EN 12385-5 for lifts.

**Marking:** According to standard

**Standard:** EN 13411-7

*DIN 15315 replaced by EN 13411-7*



| Код товара | Rope Ø range mm | Finish     | B1 mm | B2 mm | B3 mm | C mm | D mm | E mm | H1 mm | H2 mm | H3 mm | R mm | S mm | Bec kg |
|------------|-----------------|------------|-------|-------|-------|------|------|------|-------|-------|-------|------|------|--------|
| KII08      | 6-8             | Galvanized | 12    | 14    | 11    | 37   | 12   | 20   | 150   | 75    | 92    | 12,5 | 4    | 0,57   |
| KII11      | 9-11            | Galvanized | 15    | 17    | 14    | 48   | 16   | 26   | 190   | 95    | 117   | 16   | 6    | 1,05   |
| KII14      | 12-14           | Galvanized | 20    | 22    | 18    | 58   | 18   | 32   | 230   | 115   | 141   | 19   | 8    | 1,89   |
| KII17      | 15-17           | Galvanized | 23    | 25    | 21    | 70   | 22   | 36   | 260   | 130   | 162   | 23   | 10   | 3,26   |
| KII20      | 18-20           | Galvanized | 26    | 27    | 24    | 82   | 25   | 40   | 300   | 150   | 186   | 26   | 12   | 5,25   |

## Blueprint

