



Master Link Pewag AWI Stainless

Product information



Stamped and suitable for both I- and II-leg assemblies and wire rope slings (similar to DIN 3088- 1989). The master link may also be used in VWI four-leg assemblies and as an end link. Its dimensions are similar to DIN 5688-1 and it is tested at 100 % of its load capacity.

A particular bonus is the higher resistance to acids and caustics compared to the standard loading rings G8, G10 and G12.

The AWI Master link is particularly suited for use in water and wastewater applications. It can also be used in connection with chemicals and food products; however, restrictions will apply.

Marking: CE-marked

Safety factor: 4:1

Класс: 6

Код товара	Код	WLL ton	Usable with sling hooks up to DIN 15401 No.	For chain Ø 1-leg mm	For chain Ø 2-leg mm	Double hook DIN 15402 no.	d mm	s mm	t mm	w mm	Bec kg	Delivery time
NORHK86	AWI 13-6	1,6	2,5	6/7/8	6	4	13	10	110	60	0,34	0
NORHK108	AWI 16-6	2,6	2,5	10	7/8	4	16	14	110	60	0,53	0
NORHK1310	AWI 18-6	3,5	5	-	10	6	18	14	135	75	0,83	0
NORHK1613	AWI 22-6	6,3	6	13/16	13	8	23	17	160	90	1,55	0

Blueprint

