

Steel wire rope winches with top handle

Produktinformation



Steel wire rope winch for lifting and pulling. Equipped with a two way friction brake. The winch can be attached in many different ways to e.g. wall or floor.

Product is delivered without steel wire rope which can be ordered separately.

WIRE ROPES WITH SWIVEL LATCH HOOK


Suits for winch	Length	Wire diameter	Product code
VAVIN250Y	12 m	4 mm	VAVIN250VA412
VAVIN500	14 m	6 mm	VAVIN500VA614
VAVIN1000Y	30 m	10 mm	VAVIN100VA1030

... [Read more](#)

Märkning: Enligt standard, CE-märkning
Standard: EN 13157

Steel wire rope winches with top handle

Ritning & mått



Lyfttabell

Art.nr	Max last (WLL) ton	Lina Ø mm	Max. pulling capacity kg	Gear ratio	Rope capacity m	A mm	B mm	C mm	D mm	E mm	G mm	H mm	I mm	JØ mm	Vikt kg
VAVIN250Y	0,125	4-5	250	15:1	20	150	330	150	200	240	128	136/100	114	11	10
VAVIN500Y	0,25	6	500	21:1	25	180	360	180	260	240	182	183/130	141	13	17
VAVIN1000Y	0,5	9-10	1 000	26:1	30	300	490	300	300	350	198	247	186	17	35