



Steel wire rope winches with top handle

Produktinformation

Steel wire rope winch for lifting and pulling. Equipped with a two way friction brake. The winch can be attached in many different ways to e.g. wall or floor.

Product is delivered without steel wire rope which can be ordered separately.

WIRE ROPES WITH SWIVEL LATCH HOOK

Suits for winch	Length	Wire diameter	Product code
VAVIN250Y	12 m	4 mm	VAVIN250VA412
VAVIN500	14 m	6 mm	VAVIN500VA614
VAVIN1000Y	30 m	10 mm	VAVIN100VA1030

Märkning: Enligt standard, CE-märkning

Standard: EN 13157

Art.nr	Max last (WLL) ton	Lina Ø mm	Max. pulling capacity kg	Gear ratio	Rope capacity m	A mm	B, mm	C, mm	D mm	E, G, mm	H, mm	I mm	J Ø mm	Vikt kg	Ca. levtid (arbetsdagar)	
VAVIN250Y	0,125	4-5	250	15:1	20	150	330	150	200	240	128	136/100	114	11	10	1
VAVIN500Y	0,25	6	500	21:1	25	180	360	180	260	240	182	183/130	141	13	17	1
VAVIN1000Y	0,5	9-10	1 000	26:1	30	300	490	300	300	350	198	247	186	17	35	1

Ritning & mått

