



## Hydraulic bottle jack

### Produktinformation

On top of the cylinder is rotated shim (2- 20t), which provide to get more height. The jack is packed in a stylish storage package.

**Märkning:** CE-märkning

Art.nr	Benämning	Max last (WLL) ton	Min. höjd mm	Amm mm	B, mm	C mm	Dmm mm	E mm	F mm	Vikt kg	Ca. levtid (arbetsdagar)
TUNKKI20P	TUNKKI20P	2	168	168	100	48	316	94,5	78	2,35	1
TUNKKI50P	TUNKKI50P	5	207	207	125	70	402	117	97	3,9	14
TUNKKI100P	TUNKKI100P	10	222	222	145	80	450	124	106	5,2	1
TUNKKI10PM	TUNKKI10PM	10	125	125	90	-	215	165	160	7,7	1
TUNKKI160P	TUNKKI160P	15	227	227	150	80	457	141	118	7,9	1
TUNKKI200P	TUNKKI200P	20	235	235	150	60	445	152	124	9,7	1
TUNKKI20PM	TUNKKI20PM	20	150	150	95	-	245	186	175	11,2	1
TUNKKI300P	TUNKKI300P	32	260	260	160	-	420	185	165	17,8	1
TUNKKI500P	TUNKKI500P	50	280	280	170	-	450	207	185	25,8	1

## Ritning & mått

