

Hydraulic bottle jack

Produktinformation




On top of the cylinder is rotated shim (2- 20t), which provide to get more height. The jack is packed in a stylish storage package.

... [Read more](#)

Märkning: CE-märkning

Hydraulic bottle jack

Ritning & mått



Lyfttabell

Art.nr	Benämning	Max last (WLL) ton	Min. höjd mm	A mm	B mm	C mm	D mm	E mm	F mm	Vikt kg
TUNKKI20P	TUNKKI20P	2	168	168	100	48	316	94,5	78	2,35
TUNKKI50P	TUNKKI50P	5	207	207	125	70	402	117	97	3,9
TUNKKI100P	TUNKKI100P	10	222	222	145	80	450	124	106	5,2
TUNKKI10PM	TUNKKI10PM	10	125	125	90	-	215	165	160	7,7
TUNKKI160P	TUNKKI160P	15	227	227	150	80	457	141	118	7,9
TUNKKI200P	TUNKKI200P	20	235	235	150	60	445	152	124	9,7
TUNKKI20PM	TUNKKI20PM	20	150	150	95	-	245	186	175	11,2
TUNKKI300P	TUNKKI300P	32	260	260	160	-	420	185	165	17,8
TUNKKI500P	TUNKKI500P	50	280	280	170	-	450	207	185	25,8