



Tiger winches

Produktinformation

High quality Tiger winch is suitable for both lifting and pulling.

The winch is equipped with an automatic brake function which ensures that there is no risk of load falling or sliding. Brake system and components are encased and protected from dust and rain.

Straps and wire ropes are also available separately as spare parts.

Steel wire rope or strap need to order separately.

Product equipped with wire rope can be used for lifting and pulling and product with strap only for pulling. Check the ropes and traps from technical data tab.

All the dimension data can be found on the documents tab

Märkning: Enligt standard

Standard: EN 13157

| Art.nr | Max last (WLL) ton | Gear ratio | Length handle mm | Drum diameter mm | Rope capacity m | Pulling capacity t | Längd på bandsling m | Vikt kg | Ca. levtid (arbetsdagar) |
|-----------|-----------------------|------------|---------------------|---------------------|--------------------|-----------------------|-------------------------|------------|--------------------------|
| VINTT360 | 0,185 | 4,1:1 | 160 | 40 | 36 | 0,37 | 9,1 | 3 | 1 |
| VINTT550 | 0,275 | 4,1:1 | 210 | 50 | 23 | 0,55 | 8,5 | 3,5 | 1 |
| VINTT800 | 0,41 | 5:01 | 320 | 70 | 24 | 0,82 | 14,1 | 8 | 1 |
| VINTT1180 | 0,6 | 10:01 | 320 | 82 | 18 | 1,2 | 10,6 | 10,5 | 1 |