



Lever hoists

Produktinformation

Haklift Lever Hoist is a hoist of high quality, it is durable and easy to operate using the ergonomic ratchet lever. Construction is compact and light weight. The standard lifting height is 3 m. Other lifting heights are also available with fast delivery time from stock.

Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- The unique surface treatment gives excellent corrosion protection and low operating volume
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection, HF -13,56 Mhz
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available

Märkning: Enligt standard, CE-märkning

Standard: EN 13157

Art.nr	Max last (WLL) ton	Lyfthöjd m	Number of falls	Lyftkätting mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Vikt kg	Ca. levtid (arbetsdagar)
VTHA250	0,25	3	1	4 x12	100	70	56	163	20	31	235	3	1
VTHA500	0,5	3	1	5 x 15	150	90	118	253	22	32	310	6,3	1
VTHA800	0,8	3	1	5,6 x 17	158	98	132	273	23	36	340	7,5	1
VTHA1600	1,6	3	1	7,1 x 21	185	111	145	378	29	43	400	11,9	1
VTHA3200	3,2	3	1	10 x 28	212	124	198	418	37	50	520	25,3	1
VTHA6300	6,3	3	2	10 x 28	212	124	230	418	43	53	640	40,6	10
VTHA9000	9	3	3	10 x 28	212	124	338	418	44	67	730	54,9	1

Ritning & mått

