

## Lever hoists

### Produktinformation



Haklift Lever Hoist is a hoist of high quality, it is durable and easy to operate using the ergonomic ratchet lever. Construction is compact and light weight. The standard lifting height is 3 m. Other lifting heights are also available with fast delivery time from stock.

#### Features:

- Each hoist is dynamic proof load tested 1,5 x WLL before leaving the factory
- Sprocket wheel equipped with needle bearings and drive shaft supported by needle bearing and slide bearing inside to ensure smooth and efficient operation
- Safe, well covered automatic load reaction brake
- Equipped with 2 brake pawls and 4 brake springs (double safety compared to EN 13157 requirement)
- The unique surface treatment gives excellent corrosion protection and low operating volume
- Swivel hooks at both ends makes in line positioning easy
- Hooks are designed to open at overload instead of breaking
- Hooks fitted with heavy duty steel safety latches
- Hook have Deformation Check Dots forged into side for overload detection
- RFID equipped (chip) for easy service and inspection, HF -13,56 Mhz
- Test certificate and Declaration of Conformity enclosed with each hoist
- Spare parts available


... [Read more](#)

**Märkning:** Enligt standard, CE-märkning

**Standard:** EN 13157

## Lever hoists

### Ritning & mått



### Lyfttabell

Art.nr	Max last (WLL) ton	Lyfthöjd m	Antal kättingfall	Lyftkätting mm	A mm	B mm	C mm	D mm	E mm	F mm	H mm	Vikt kg
VTHA250	0,25	3	1	4 x 12	100	70	56	163	20	31	235	3
VTHA500	0,5	3	1	5 x 15	150	90	118	253	22	32	310	6,3
VTHA800	0,8	3	1	5.6 x 17	158	98	132	273	23	36	340	7,5
VTHA1600	1,6	3	1	7.1 x 21	185	111	145	378	29	43	400	11,9
VTHA3200	3,2	3	1	10 x 28	212	124	198	418	37	50	520	25,3
VTHA6300	6,3	3	2	10 x 28	212	124	230	418	43	53	640	40,6
VTHA9000	9	3	3	10 x 28	212	124	338	418	44	67	730	54,9