



## Geared trolley

### Produktinformation

Geared trolley for IPE and T beams. The trolley moves on the beam by pulling the hand chain. The wheels are equipped with duration lubricated ball bearings. The width of the trolley can be adjusted by a threaded rod (10 and 20 t models with washers, in the picture). The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

**Märkning:** Enligt standard, CE-märkning

**Standard:** EN 13157

**Säkerhetsfaktor:** 4:1

Art.nr	Max last (WLL) ton	Beam width mm	Min. kurvradie mm	A mm	B, C,	D mm	E,	F, G,	H,	J,	Vikt kg	Ca. levtid (arbetsdagar)
SIVA05HKS	0,5	50-220	500	352,5	198 158	12,5	40	~3 55	75	28	8,5	1
SIVA05HLKS	0,5	50-305	500	437,5	198 158	12,5	40	~3 55	75	28	8,9	1
SIVA10HKS	1	58-220	700	353,5	238 183	17	31	~3 68	95	37	12,5	1
SIVA10HLKS	1	58-305	700	438,5	238 183	17	31	~3 68	95	37	13	1
SIVA20HKS	2	66-220	900	362	277 208	20	31	~3 80	108	48	17	1
SIVA20HLKS	2	66-305	900	447	277 208	20	31	~3 80	108	48	17,8	1
SIVA30HKS	3	74-220	1 200	406,5	324 249	26	31	~3 100	131	56	28	1
SIVA30HLKS	3	74-305	1 200	491,5	324 249	26	31	~3 100	131	56	29,1	1
SIVA50HKS	5	90-220	1 000	434,5	373 296,5	28	40	~5 120	154	65	45	1
SIVA50HLKS	5	90-305	1 000	519,5	373 296,5	28	40	~5 120	154	65	46,1	1
SIVA100HKS	10	125-203	1 300	487,5	455 490	82	36,5	~5 - -	-	120	93	1
SIVA100HLKS	10	125-305	1 300	589,5	455 490	82	36,5	~5 - -	-	120	95	1
SIVA200HKS	20	136-203	4 700	523	642 622	110	54	~5 - -	-	150	247,5	1
SIVA200HLKS	20	136-305	4 700	625	642 622	110	54	~5 - -	-	150	250	1

## Ritning & mått

